

Product Data Sheet

Date 02/2020 Supersedes: NEW

3M I.D. Number	255P
Product Description	255P is designed as a general purpose product intended for use on soft-wood, metal and plastics.
Mineral	Aluminum oxide mineral
Grades	P80, P100, P120, P150, P180, P220, P240, P320, P360, P400, P500, P800
Bond	Resin bonded with FreCut™
Backing	C Paper
Available Forms	Hookit™ & Stickit™ Discs, Sheets and Roll
Identification	All relevant product identification information can be found on the product label or on the box in which the product was received or on the with the product supplied Safety Instruction Leaflet.
Storage	Store at 16 °C – 26 °C and 35-50 % relative humidity in its original box on "first-in - first-out" cycle. Note: The shelf life may be shortened if the original packaging is not properly sealed or stored in an environment with high temperatures or humidity.
Precautionary Information	Refer to Product Label and Safety Instruction Leaflet for health and safety information before using the product. <u>This product should be used on guarded tool with 3M Hookit backup pad.</u> For information please contact your local 3M Office. <u>www.3M.com</u>
For Additional Information	To request additional product information or to arrange for sales assistance, call your local 3M Application Engineering.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark of the 3M Company

3M Nederland B.V. Abrasives Systems Division Molengraaffsingel 29 2629 JD Delft NEDERLAND

www.3M.nl/abrasives