



Reach Normally Inaccessible Areas

- Grind, deburr, blend and polish, on metal, plastic, fiberglass, composites, rubber, glass and more. Grind from contact wheel or platen pad; finish and polish using slack of belt.
- Lightweight 7° offset design. Grinding head pivots 360° for securing in most efficient position.
- Ergonomic "soft touch" grip.
- Belt guard easily detaches for quick abrasive change; simple belt tracking adjustment knob.



Model 40320

FOR ABRASIVE BELTS
1/8" - 3/4" wide x 18" long
(3 mm - 19 mm x 457 mm)
SEE PAGE 270

Model 40320 For 18" Long Belts

- Includes 11206 Contact Arm for 3/4" wide x 18" long belts (see page 16).
- USA Government National Stock Number 3419015023640.

Model 40335 For 18" Long Belts

- Includes 11203 Contact Arm for 1/2" wide x 18" long medium non-woven nylon belt (78020).
- Excellent for setting grain lines, achieving consistent satin finish on metals, removing oxide and weld discoloration.

Model 40381 Slow Speed, For 18" Long Belts

- 1,500 SFPM. Slow speed ensures longer belt life when working on titanium and other exotic materials.
- Includes 11206 Contact Arm for 3/4" wide x 18" long belts (see page 16).

Model 40326 For 20-1/2" Long Belts

- Includes 11287 Contact Arm for 5/8" or 3/4" wide abrasive belts. (11287 is only arm that accepts 20-1/2" long belts.)

40321 Versatility Kit

- Includes 40320 Dynaflex® II with 11206 Contact Arm, plus additional 11203 and 11204 Contact Arms. Also includes eight popular abrasive belts, three platen pads, 50010 Collet (1/4") for Die Grinder use, plus 95262 and 95281 Wrenches. All contained in a durable carrying case.
- USA Government National Stock Number 5130012794907.

40324 Versatility Kit Metric

- Includes 40320 Dynaflex® II with 11206 Contact Arm, plus additional 11203 and 11320 Contact Arms. Also includes eight popular abrasive belts, three platen pads, 50015 Collet (6 mm) for Die Grinder use, plus 95262 and 95281 Wrenches. All contained in a durable carrying case.



Slack of abrasive belt is used to efficiently polish radiused area.



Optional 11200 Stroke Sander Arm leaves in-line scratch pattern.



Dynaflex® II easily converts to a Die Grinder with optional 50010 Collet (1/4") or 50015 Collet (6 mm). To convert to a Drill, order 53032 Chuck (1/4").

Model 40321



| Model Number | Motor hp (W) | Motor RPM | Sound Level | Abrasive Belt Size Inch (mm) | Max. Air Flow SCFM (L/Min) | Max. SFPM (SM/Min) | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-----------------------------------|----------------------------|--------------------|-------------------|------------------|------------------|
| 40320 | .5 (373) | 20,000 | 80 dB(A) | 1/8-3/4 (3-19) W x 18 (457) L | 28 (793) | 4,550 (1,382) | 2.5 (1.1) | 14-1/4 (362) | 4-7/8 (124) |
| 40326 | .5 (373) | 20,000 | 80 dB(A) | 1/8-3/4 (3-19) W x 20-1/2 (521) L | 28 (793) | 4,550 (1,382) | 2.5 (1.1) | 14-1/4 (362) | 4-7/8 (124) |
| 40335 | .5 (373) | 20,000 | 80 dB(A) | 1/8-3/4 (3-19) W x 18 (457) L | 28 (793) | 4,550 (1,382) | 2.5 (1.1) | 14-1/4 (362) | 4-7/8 (124) |
| 40381 | .4 (298) | 5,000 | 82 dB(A) | 1/8-3/4 (3-19) W x 18 (457) L | 24 (680) | 1,500 (457) | 2.8 (1.2) | 15-1/2 (394) | 5-3/4 (146) |

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 3/8" (10 mm) • Air Pressure 90 PSIG (6.2 Bar)

Tune-Up Kits: Models 40320, 40326, 40335 – No. 96044; Model 40381 – No. 96174 (page 267)